



	Xceed 1	Xceed 2	Xceed 3	
Speech Understanding	OpenSound Navigator™	Level 1	Level 2	-
	- Balancing power effect	100%	50%	-
	- Max. noise removal	9 dB	5 dB	-
	OpenSound Optimizer™	•	•	•
	Noise Reduction LX	-	-	•
	Multiband Adaptive Directionality LX	-	-	•
	OpenSound Booster™	•	•	-
	Speech Guard™ LX	Level 1	Level 3	-
	Single compression LX	-	-	•
	Speech Rescue™ LX	•	•	•
Sound Quality	Clear Dynamics	•	-	-
	Spatial Noise Management	•	-	-
	Processing Channels	48	48	48
	Bass Boost (streaming)	•	•	•
Listening Comfort	Transient Noise Management	4 configurations	3 configurations	-
	Feedback shield LX	•	•	•
	Wind Noise Management	•	•	•
Personalization & Optimizing Fitting	YouMatic™ LX, NR levels	3 configurations	2 configurations	-
	Fitting Bands	14	12	8
	Multiple Directionality Options	•	•	•
	Adaptation Management	•	•	•
	Oticon Firmware Updater	•	•	•
	VC range and step size	•	•	•
Connecting to the World	Fitting Formulas	DSE, VAC+, NAL-NL1 + 2, DSL v5.0	DSE, VAC+, NAL-NL1 + 2, DSL v5.0	DSE, NAL-NL1 + 2, DSL v5.0
	Stereo streaming (2.4 GHz)	•	•	•
	Oticon ON App	•	•	•
	ConnectClip	•	•	•
	Remote Control 3.0	•	•	•
	TV Adapter 3.0	•	•	•
	Phone Adapter 2.0	•	•	•
	Amigo FM	•	•	•
	Tinnitus SoundSupport™	•	•	•
	CROS/ BiCROS support	•	•	•
Bimodal fitting panel	•	•	•	

Oticon Xceed BTE UP is an ultra power hearing aid with a 675 battery. The style has separate push buttons for programs and volume for easy usage and control. It features T-coil, optional LED indications and FM support.

OpenSound Navigator helps power users to select and understand speech even in challenging sound environments by balancing the sound sources and suppressing background noise.


OpenSound Optimizer enhances both listening experience and comfort by blocking feedback and allowing the users to receive prescribed gain.

TwinLink wireless technology combines binaural communication and streaming, and 2.4 GHz connectivity for stereo streaming directly from digital sound sources.

Oticon Xceed is built on the Velox S platform using a programmable firmware architecture supporting future performance updates.

Operating conditions
 Temperature: +34°F to +104°F
 Relative humidity: 5% to 93%, non-condensing

Storage and transportation conditions
 Temperature and humidity should not exceed the following limits for extended periods during transportation and storage.
 Temperature: -13°F to +140°F
 Relative humidity: 5% to 93%, non-condensing



For information on compatibility, please visit www.oticon.com/support/compatibility











Absolute Hearing Solutions LLC
absolutehearing@att.net

759 Cross Pointe Road Suite F
 Gahanna, Ohio 43230

Phone: 614-452-4260
 Toll Free: 888-803-2159
 Fax: 614-577-0481

www.absolutehearing.com

Technical data		Ear Simulator Measured according to IEC 60118-0:1983/AMD1:1994, IEC 60118-0:2015, IEC 60118-1:1995+AMD1:1998 CSV and IEC 60318-4:2010	2CC Coupler Measured according to ANSI S3.22-2014, IEC 60118-0:2015 and IEC 60318-5:2006
 <p>120</p>  <p>DSE Fitting Range Hook, undamped</p>		<p>OSPL90</p>  <p>Full-on Gain</p>  <p>Frequency Response</p> 	<p>OSPL90</p>  <p>Full-on Gain</p>  <p>Frequency Response</p> 
		<p>Peak OSPL90 1600 Hz 146 dB SPL</p> <p>HFA-OSPL90 138 dB SPL</p> <p>Peak Full-on gain¹ 1600 Hz 87 dB</p> <p>HFA-FOG 77 dB</p> <p>Reference test gain 61 dB</p> <p>Frequency range 100-6000 Hz</p> <p>Telecoil output (1600 Hz) 1 mA/m field 111 dB SPL 10 mA/m field 126 dB SPL</p> <p>SPLITS L/R -</p> <p>Total harmonic distortion (Input 70 dB SPL) 500 Hz 11 % 800 Hz <2 % 1600 Hz 3 %</p> <p>Equivalent input noise level Omni 19 dB SPL Dir 35 dB SPL</p> <p>Battery consumption² Typical 1.8 mA Quiescent 1.5 mA</p> <p>Battery life, artificial measurement, hours³ 370</p> <p>Expected battery life, hours (battery size 675 - IEC PR44)⁴ 80-250</p>	<p>Peak OSPL90 1600 Hz 142 dB SPL</p> <p>HFA-OSPL90 130 dB SPL</p> <p>Peak Full-on gain¹ 1600 Hz 83 dB</p> <p>HFA-FOG 69 dB</p> <p>Reference test gain 53 dB</p> <p>Frequency range 100-5300 Hz</p> <p>Telecoil output (1600 Hz) 1 mA/m field - 10 mA/m field -</p> <p>SPLITS L/R 112 dB SPL</p> <p>Total harmonic distortion (Input 70 dB SPL) 500 Hz 9 % 800 Hz <2 % 1600 Hz 3 %</p> <p>Equivalent input noise level Omni 23 dB SPL Dir 38 dB SPL</p> <p>Battery consumption² Typical 4.1 mA Quiescent 1.5 mA</p> <p>Battery life, artificial measurement, hours³ 160</p>

1) Measured with the gain control of the hearing aid set to its full-on position minus 20 dB and with an input SPL of 70 dB. This is to obtain a gain response equal to the full-on gain response from e.g. IEC 60118-0+A1:1994 but without influence of feedback.

2) Battery current is measured according to IEC 60118-0:1983/AMD1:1994 §7.11, IEC 60118-0:2015 §7.7 and ANSI S3.22:2014 §6.13 after a settling time of minimum 3 minutes.

3) Based on the standardized battery consumption measurement (IEC 60118-0:1983/AMD1:1994). The actual battery life depends on battery quality, use pattern, active feature set, hearing loss and sound environment.

4) Real usage battery life is shown as an estimated interval based on mixed use cases with variable amplification settings and variable input levels, incl. direct stereo streaming from a TV (25% of the time) and streaming from a mobile phone (6% of the time).