

ReSound ENZO Q™

Call
Absolute Hearing Solutions
For Hearing Aid Details!
614-452-4280
www.absolutehearingsolutions.com



Absolute Hearing Solutions LLC
absolutehearing@att.net

759 Cross Pointe Road Suite F
Gahanna, Ohio 43230

Phone: 614-452-4280
Toll Free: 888-803-2159
Fax: 614-577-0481
www.absolutehearingsolutions.com



Product Description

Based on our most powerful chip platform yet, the ReSound ENZO Q hearing solution is so much more than just super power hearing aids. Utilizing the unique combination of our renowned ReSound audiological heritage, including Binaural Directionality III, Spatial Sense, and our best-in-class feedback system with new Impulse Noise Reduction, the solution provides clear, comfortable, high-quality sound in any environment.

ReSound ENZO Q is a 6th generation, 2.4 GHz wireless hearing aid that offers direct audio streaming from iOS and Android™* devices.


With ReSound Assist and the ReSound Smart 3D™ app, you can provide remote fine-tuning services for your clients.

The Behind-the-Ear (BTE) model 88 hearing aid comes with telecoil and Direct Audio Input (DAI) functionality as standard, and it also supports the full line of ReSound wireless accessories.

ReSound ENZO Q BTE hearing aids are iSolate™ nanotech-coated for optimum durability and meet the IP68 classification for ingress protection.

*Compatible from Android version 10 and Bluetooth® 5.0 with the Android streaming to hearing aids feature.

Fitting Range




Model	EQ988-DWHT	EQ788-DWHT	EQ588-DWHT
Device Configurations			
Battery size	13		
Colors available	13		
Audiological Features			
WARP compression (WDRC) - number of channels	17	14	12
Binaural Directionality III	●	-	-
Spatial Sense	●	-	-
Binaural Directionality	-	●	-
Natural Directionality II	●	●	●
Directional Mix Processor	●	●	●
Adjustable directional mix	●	-	-
Synchronized Soft Switching	●	●	-
Soft Switching	●	●	●
Autoscope Adaptive Directionality	●	-	-
Multiscope Adaptive Directionality	-	●	-
Adaptive Directionality	-	-	●
Binaural Environmental Optimizer II	●	-	-
Environmental Optimizer	-	●	-
Noise Tracker II	●	⊙	○
Expansion	●	⊙	○
Impulse Noise Reduction	●	●	-
Wind Guard	●	⊙	○
Sound Shaper	●	●	●
DFS Ultra II	●	●	●
Music Mode	●	●	●
Synchronized Acceptance Manager	●	●	●
Low Frequency Boost	●	⊙	○
Amplification Strategy (WDRC/Semi-Linear/Linear)	●	●	⊙
Tinnitus Sound Generator	●	●	●
Functional Features			
Synchronized Push Button	●	●	●
Synchronized Volume Control	●	●	●
Smart Start	●	●	●
Phone Now	●	●	●
Comfort Phone	●	●	●
Ear to Ear Communication	●	●	●
Direct Audio Streaming	●	●	●
ReSound TV Streamer 2, Remote Control, Remote Control 2, Phone Clip+, Micro Mic and Multi Mic	●	●	●
ReSound Smart 3D™ app	●	●	●
ReSound Assist			
Remote Fine Tuning	●	●	●
Remote Firmware Updates	●	●	●
Fitting Features			
ReSound Smart Fit™ 1.6 or higher	●	●	●
Fully Flexible Programs	4	4	4
Auto DFS	●	●	●
Onboard Analyzer II	●	●	●
Wireless Fitting with Noahlink Wireless	●	●	●

○ Basic

⊙ Advanced

● Ultimate



© 2019 GN Hearing A/S. All rights reserved. ReSound is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad and iPod touch are trademarks of Apple Inc., registered in the US and other countries. Android is a trademark of Google LLC. The Bluetooth word mark and logos are registered trademarks owned by Bluetooth SIG, Inc.

Technical Specifications

EQ88-DWHT		IEC 60118-0 2nd IEC 711 Ear Simulator	IEC 60118-0 3rd IEC 60118-7 ANSI S3.22 2cc coupler	
-----------	--	---	---	--

Reference test gain (60 dB SPL input)	1600 Hz/HFA	60	53	dB
Full-on gain (50 dB SPL input)	Max. 1600 Hz/HFA	80 73	73 67	dB
Maximum output (90 dB SPL input)	Max. 1600 Hz/HFA	141 135	134 130	dB SPL
Total harmonic distortion	500 Hz	1.4	2.8	%
	800 Hz	0.6	0.4	
	1600 Hz	0.8	0.4	
	3200 Hz	-	0.1	
Telecoil sensitivity (1 mA/m input)	Max.	110	103	dB SPL
HFA - SPLIV @ 31.6 mA/m (ANSI)	HFA	123	114	
Full-on telecoil sensitivity @ 1mA/m	1600 Hz/HFA	104	98	
Equivalent input noise, w/o noise reduction		23	22	dB SPL
1/3 Octave Equivalent input noise, w/o noise reduction		13	12	dB SPL
Frequency range IEC 60118-0: 2015		100-5270*	100-4940	Hz
Current Drain (Quiescent/Operating)		1.18/1.4	1.18/1.4	mA

* Measured according to IEC60118-0:2015, with 711 Ear Simulator coupler.






ANSI S3.22-2014
IEC 60118-0:2015
JIS C 5512: 2015
2cc coupler

IEC 60118-0: 1983_AMD1:1994
IEC 711 Ear Simulator

Data compliant with IEC60118-0 Edition3.0 2015-06,
IEC60118-7 and ANSI S3.22-2009, supply Voltage 1.3V

Patents pending

All specifications are subject to change without notice



40123701US CA VA-2003-Rev.C

Manufacturer according to FDA:

GN ReSound North America
8001 E Bloomington Freeway
Bloomington, MN 55420
USA
1-888-735-4327
resound.com

Manufacturer according to FDA:

ReSound Government Services
8001 E Bloomington Freeway
Bloomington, MN 55420
USA
1-800-392-9932
resound.com/veterans

Manufacturer according to Health Canada:

ReSound Canada
2 East Beaver Creek Road, Building 3
Richmond Hill, ON L4B 2N3
Canada
1-888-737-6863
resound.com