ESOUND GN

^{Made for} **€** iPhone | iPad | iPod

Works with and roid

ReSound LiNX Quattro[™]

Confidence in the finer details



GN Making Life Sound Better FOR 150 YEARS

Introducing ReSound LiNX Quattro™

Confidence shines through the finer details. ReSound LiNX Quattro combines brilliant sound quality, an unrivaled full spectrum of streaming, support and personalization with ReSound Assist and the world's most advanced rechargeable solution – all in one product.

ReSound LiNX Quattro offers a brilliant experience beyond compare to inspire confidence in the moments that matter most.

Brilliant sound experience

CLEARER SOUNDS

With the highest input dynamic range, ReSound LiNX Quattro leverages the full range of the MEMs microphone allowing sound to be passed to our amplifier without being altered. Therefore, sound is processed in a cleaner way - free of distortion.

FULLER SOUNDS

A broader frequency response means patients will hear a larger range of sounds and will have access to nuances in tones that were previously unavailable to them.

RICHER EXPERIENCE

With clearer and fuller sounds coupled with a new radio for improved ear-to-ear performance and decreased lag time in streaming, patients will receive the most brilliant sound experience yet.

RIE STYLES





BTE STYLES



 Mini BTE 67
 BTE 77
 Power BTE 88

 NEW!
 NEW!
 NEW!

CUSTOM STYLES



2.4 GHZ MIH Wireless CIC ITC ITE-HS ITE-FS Now with optional Telecoil

NEW! Chip platform takes sound quality to the next level

MORE SPEED, MORE MEMORY, MORE POWER - MORE CONFIDENCE

The brand new chip delivers twice the memory, 100% more speed, 30% more computing power and a new radio with 20% reduced power consumption. Together with an extended dynamic range, improved frequency response, a stronger wireless signal strength for enhanced ear-to-ear performance and localization of sound, ReSound LiNX Quattro delivers our most clear, natural sound yet.

116 dB SPL


The highest input dynamic range and the first hearing aid to utilize the full range of the MEMs microphones means loud inputs are more clear and softer sounds are available with less background noise.

$9.5 \,\mathrm{kHz}$

Extended frequency bandwidth provides patients with access to more nuances of sound and allows for better sound balance across frequencies - even when streaming.

5 dB

New radio with 5 dB improved signal strength enhances ear-to-ear wireless performance, allowing Spatial Sense to sharpen and increase localization cues.



Sound with virtually no limits

resound gn MORE LOCALIZATION CUES WITH SPATIAL SENSE

With the advanced performance of the new chip platform, our Spatial Sense feature is now better than ever. More high-frequency cues are available to help your patients localize sounds to the front and back. Spatial Sense can also measure the interaural level difference within less than a 1 dB tolerance. This is crucial because accurate level cues that align with timing cues enhance spatial hearing for the most natural sound quality.


BEST SOUND QUALITY

Hearing aids are designed to amplify speech, but music serves as the ultimate test of sound quality. It has high, intense peaks, and is often enjoyed at a higher volume. With ReSound LiNX Quattro, the dynamics of music are preserved and reproduced with a fuller sound quality.

Below is a waveform of classical violin music, with a typical input dynamic range and with the higher range of ReSound LiNX Quattro.

REDUCED RANGE

HIGHEST RANGE



ReSound LiNX Quattro is preferred 95% of the time for music listening, compared to other premium hearing aids*.

* Jespersen et al. 2018.


Unrivaled full spectrum of streaming

EXCEPTIONAL STREAMING FROM ANY AUDIO SOURCE

Patients can now stream sound in stereo directly to iOS and Android[™]* devices without the need for an intermediary device.

BROADEST MFI STREAMING BANDWIDTH

With a frequency bandwidth that expands up to 9.5 kHz, the widest among MFi hearing aids, users get a fuller quality for sound streamed from ReSound LiNX Quattro.



ReSound **LiNX Quattro**

All other premium MFI hearing aids

Source: Groth. 2018

9.5kHz

A CLEAR NUMBER ONE FOR STREAMING


ReSound LiNX Quattro was top-rated for sound quality when streaming from an iPhone. Hearing impaired listeners rated ReSound LiNX Quattro 37% better on average compared to other premium hearing aids.**



** Aranda de Toro and Groth. 2019

TOP CHOICE FOR TV

Listeners preferred the sound quality with ReSound LiNX Quattro 71% of the time when streaming directly from the ReSound TV Streamer 2 compared to other premium hearing aids and their respective TV streaming devices.







*Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer and service carrier. ReSound cannot guarantee compatibility with all Android devices.

Support and personalization

Patients can easily and discreetly control their hearing aids right from their phone with the ReSound Smart 3D app. ReSound LiNX Quattro patients have access to all of the current features in the ReSound Smart 3D app in addition to:

- Rechargeable battery status

- Mix-in streaming volume control





Download on the App Store




ReSound Assist allows you to offer flexible and accessible care to your patients with Live Assistance and remote fine-tuning

ReSound Assist Live makes it possible to offer patients online, face-to-face fitting appointments. Connect with a video call to remotely fine-tune your patients' hearing aids directly from your ReSound Smart Fit™ software.

For extra support, patients can also submit a remote fine-tuning request right from their ReSound Smart 3D app. Using ReSound Smart Fit software, you can send your recommended adjustments back to them at your convenience.





The world's most advanced rechargeable solution


INTRODUCING LONG-LASTING POWER IN A SMALL SIZE

ReSound LiNX Quattro now introduces the most advanced rechargeable hearing aid. With a completely sealed lithium-ion battery, a small, discreet size and long-lasting battery power, your patients can rely on their hearing aids for more than a full day.

SLEEK AND DISCREET PORTABLE CHARGING CASE

Inductive charging makes it easy to securely place the hearing aids in the case for charging, without having to worry about contacts. In addition, the portable charging case holds an additional three full charges, so patients have the freedom to charge their hearing aids anywhere. Upon insertion or removal of hearing aids, the current battery status is indicated for 5-10 seconds









Charger battery status indicators

FULL CONFIDENCE WITH A COMPLETE CHARGE

No instructions needed – your patients can place their hearing aids into the simple-to-use charger, and in a few hours they can enjoy 24 hours of battery life – even when streaming television, music or other audio half of the time. Patients can easily see the battery status of their hearing aid on the ReSound Smart 3D app, and will get a notification when the rechargeable battery is running low.

REFRESH WITH A QUICK CHARGE

If your patients are on-the-go, traveling or if they forget to charge overnight, they can still access quick and long-lasting power throughout their day.



NS PUROS

ReSound Smart Fit[™]

Intuitively supporting all features

THE FUTURE-PROOF CHOICE

To ensure optimal functionality and the best possible experience, users of ReSound LiNX Quattro can get their hearing aids updated with the latest software if activated in ReSound Smart Fit. Updates can be completed easily in your clinic through the ReSound Smart Fit Fitting Software or remotely via ReSound Assist in the ReSound Smart 3D app.

ON-SCREEN RECHARGEABLE BATTERY STATUS

During the fitting, it's now easy to keep track of the battery status for your patients' rechargeable hearing aids from the on-screen display.

IMPULSE NOISE REDUCTION

Impulse Noise Reduction smooths the peaks of transient sounds and is adjustable to meet individual noise sensitivities to sudden and brief loud sounds (Off, Mild, Moderate, Strong).

FREQUENCY RESPONSE CONTROL

With the hearing aid bandwidth now extended to 9.5 kHz, all fitting prescriptions have been updated, and an additional control is available at high frequencies to optimize the response.

'VERY MILD' SOUND SHAPER OPTION

Sound Shaper is now available in a 'very mild' setting that uses a cut off frequency of 5 kHz and an output bandwidth up to 8.5 kHz.

A CONFIDENT FITTING EXPERIENCE - FROM THE FIRST FIT

ReSound Smart Fit 1.6 is compatible with the industry-standard Noahlink Wireless. Robust, fast and intuitive, it supports the easiest and most comfortable fit for ReSound hearing aids.



Your patients can hear sounds from all sides and focus on the sounds that are important, without losing touch with what's going on around them.

SPATIAL SENSE spatial hearing.

Your patients can detect where sounds are coming from, so they experience a more natural sense of their surroundings and the best possible sound quality.

NOISE TRACKER II

Your patients can get improved comfort in noisy listening situations without compromising speech understanding.

Features that support a brilliant sound experience

BINAURAL DIRECTIONALITY III

Continuous ear-to-ear exchange of data about the environment optimizes polar patterns in any listening situation.

Combines algorithms that restore pinna cues and interaural level differences to provide the brain with natural acoustic information for

BINAURAL ENVIRONMENTAL OPTIMIZER II

Works together with the Environmental Optimizer to analyze and accurately classify the listening environment, automatically adjusting gain and noise reduction settings.

Your patients can enjoy optimal audibility and listening comfort, even when moving through changing sound environments.

A unique spectral subtraction technology that reduces unwanted noise without degrading the speech signal.

IMPULSE NOISE REDUCTION

Adjustable in your fitting software, it suppresses unexpected loud sounds -like the clinking of silverware or jangling of keys - by keeping gains at prescribed levels for brief transient sounds and preserving soft transient speech sounds.

Your patients can experience more comfort with their hearing aids in environments with sudden loud sounds.

DFS ULTRA II WITH MUSIC MODE

High-precision feedback path analysis enables DFS Ultra II to cancel feedback with extreme accuracy. Music Mode analyzes the sound over a longer period of time, so the system can better distinguish true feedback from music and other tonal sounds.

Your patients can enjoy extra comfort, better audibility and all the subtle nuances of rich sound, even in more challenging situations. Music Mode provides users with a distortion-free music listening experience.

SOUND SHAPER

The only frequency compression technology that moves high-frequency sounds down in the spectrum while maintaining a proportional relationship between input and output frequencies. Also available in a 'very mild' setting that uses a cut off frequency of 5 KHz and an output bandwidth up to 8.5 KHz.

Your patients can experience improved audibility at high frequencies, particularly in speech cues, where traditional amplification is limited.

A full family of reliable and robust solutions



A PERFECT FIT WITH SUREFIT 2B RECEIVER TUBES

Our new receiver tubes fit snugly against the head and contour to the shape of the first bend in the ear canal. This helps the tube lie close to the skin and ensures the receiver fits more securely in the ear canal.

RELIABLE WITH ISOLATE NANOTECH

The ReSound LiNX Quattro RIE hearing aids are iSolate™ nanotech coated for optimum durability, and meet the IP68 classification for ingress protection.



MARKET LEADING WIRELESS ACCESSORIES

ReSound LiNX Quattro and ReSound wireless accessories work as an intelligent system for a seamless listening experience. You can offer your patients an entire ecosystem of wireless accessories to enhance their hearing experience on the phone, in noise, reverberation or over distance.







Phone and app options

iPhone

Android phones*

Other Bluetooth-er

Streaming options

STREAMER FUNCT

Power Source

Audio Quality

Voice Pickup

Telecoil

Line-in

FM compatibility (FM receiver require

Audio streaming frequency range

Compatibility overview

STREAMING, APP CONTROL AND WIRELESS ACCESSORIES

Phone		Compatible ReSound product
	Phone call	ReSound LiNX Quattro
	App use	ReSound Smart 3D
	Phone call	ReSound LiNX Quattro
	App use	ReSound Smart 3D
enabled phones	Phone call	ReSound LiNX Quattro and Phone Clip+

Overview of features in Sound Enhancer*

Available with different default settings

* Sound Enhancer available in technology level 9

Available if directionality is set to adaptive (Autoscope or SoftSwitcing)

Program	Noise	Speech	Wind	Bass/Middle/Treble
All Around	•	0	•	•
Restaurant	•	•	•	•
Outdoor	•	o	•	•
Music	•	o	•	•
Acoustic Phone	•		•	•
T-coil phone/loop (in normal program)	٠		٠	•
DAI (in normal program)	•		•	•
All streaming program	•		•	•

*Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer and service carrier. ReSound cannot guarantee compatibility with all Android devices.







	Phone Clip+	Multi Mic	Micro Mic	TV Streamer 2
101	NALITY			
	Rechargeable – portable	Rechargeable – portable	Rechargeable – portable	Wall plug-in A/C adapter – stationary
	Stereo (A2DP)	Mono	Mono	Stereo
	Directional microphone	Directional/ Omnidirectional	Directional microphone	
		•		
		•		•
ed)		•		
	A2DP streaming: 100 Hz to 10000 Hz Phone: 200 Hz to 3400 Hz	100-8000 Hz ±3 dB (Telecoil: 350-8000 Hz)	100-8000 Hz ±3 dB	100-10000 Hz

ontrol options



	ReSound Smart 3D	Phone Clip+	Remote Control 2	Remote Control
VOLUME AND PROGRAM FUNCTIONS				
Volume adjustments	Mon-/binaural	Binaural	Mon-/binaural	Binaural
Hearing aid program selection	Direct select	Toggle (1-2-3-1)	Toggle (1-2-3-1)	Toggle (1-2-3-1)
Streamer selection	Direct select		Toggle (1-2-3-1)	Toggle (1-2-3-1)
Balance hearing aid volume vs. streaming volume	•		•	
Hearing aid mute	•	•	٠	•
OTHER FUNCTIONS				
ReSound Assist	•			
Quick buttons - shortcuts to sound optimization	•			
Sound Enhancer – wind, noise, speech adjustment*	•			
Sound Enhancer – bass/middle/treble adjustment	•			
Tinnitus Manager adjustments	•			
Create favorite program with or without geo-tags	•			
Program/Streamer name customization by user	•			
Find your lost hearing aid	•			
Phone operation		•		
Display of control options	•		•	
Display battery status of rechargeable RIE 61	•			


* Available in ReSound LiNX Quattro 9

Behind the brilliant sound experience

ReSound LiNX Quattro RIEs



MODEL	RE961-DRWC RE961-DRW RE962-DRWT	RE761-DRWC RE761-DRW RE762-DRWT	RE561-DRWC RE561-DRW RE562-DRWT
DEVICE CONFIGURATIONS			
Battery size	312	le Lithium-ion for model 6´ Zinc-Air for model 61-DRW inc-Air for model 62-DRWT	/
Receiver Power levels		LP, MP, HP & UP	
AUDIOLOGICAL FEATURES			
WARP Compression (WDRC) - number of channels	17	14	12
Binaural Directionality III	•	-	-
Spatial Sense	•	-	-
Binaural Directionality	-	•	-
Natural Directionality II	•	•	•
Directional Mix Processor	•	•	•
Adjustable Directional Mix	•	-	-
Synchronized Soft Switching	•	•	-
Soft Switching	-	-	•
Autoscope Adaptive Directionality	•	-	-
Multiscope Adaptive Directionality	-	•	-
Adaptive Directionality			•
Binaural Environmental Optimizer II	•	-	-
Environmental Optimizer	-	•	-
Noise Tracker II	•	۲	0
Expansion	•	۲	0
Impulse Noise Reduction	•	•	-
Wind Guard	•	۲	0
Sound Shaper	•	•	•
DFS Ultra II	•	•	•
Music Mode	•	•	•
Synchronized Acceptance Manager	•	•	•
Low Frequency Boost (Only UP)	•	۲	0
Amplification Strategy (WDRC/Semi-Linear/Linear - Only UP)	•	•	۲
Tinnitus Sound Generator	•	•	•



	RE961-DRWC RE961-DRW RE962-DRWT	RE761-DRWC RE761-DRW RE762-DRWT	RE561-DRWC RE561-DRW RE562-DRWT
FUNCTIONAL FEATURES			,
Synchronized Push Button*	•	•	•
Synchronized Volume Control**	•	•	•
Smart Start	•	•	•
Phone Now	•	•	•
Comfort Phone	•	•	•
Ear-to-ear Communication	•	•	•
Direct Audio Streaming (iOS and Android***)	•	•	•
ReSound Wireless Accessory compatibility	•	•	•
ReSound Control™ app (Phone Clip+ is required)	•	•	•
ReSound Smart 3D™ app	•	•	•
RESOUND ASSIST			
Live Assistance	•	•	•
Remote Fine-tuning	•	•	•
Remote Firmware Updates	•	•	•
FITTING FEATURES			
Fitting Software ReSound Smart Fit™ 1.6 or higher	•	•	•
Available Gain Handles	10	8	6
Fully Flexible Programs	4	4	4
Auto DFS	•	•	•
Onboard Analyzer II	•	•	•
Noahlink Wireless	•	•	•

● Ultimate ● Advanced O Basic

* Also including functionality for synchronized Push Button Volume Control

** Only for 62 models


***Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer and service carrier. ReSound cannot guarantee compatibility with all Android devices.

ReSound LiNX Quattro BTEs


MODEL
DEVICE CONFIGURATION
Battery size
Receiver Power levels
AUDIOLOGICAL FEATURE WARP Compression (WDR number of channels Binaural Directionality III
Spatial Sense
Binaural Directionality
Natural Directionality II
Directional Mix Processor
Adjustable Directional Mix
Synchronized Soft Switchir
Soft Switching
Autoscope Adaptive Direct
1ultiscope Adaptive Direct
Adaptive Directionality
Binaural Environmental Op
Invironmental Optimizer
loise Tracker II
xpansion
mpulse Noise Reduction
Vind Guard
Sound Shaper
DFS Ultra II
1usic Mode
Synchronized Acceptance I
ow Frequency Boost (88 Amplification Strategy WDRC/Semi-Linear/Linea
innitus Sound Generator


Fitting range





Open Closed





	RE967-DWT RE977-DWT RE988-DWT	RE767-DWT RE777-DWT RE788-DWT	RE567-DWT RE577-DWT RE588-DWT					
IONS								
		312 for model 67-DWT 13 for model 77-DWT 13 for model 88-DWT						
		LP, MP, HP & UP						
URES								
VDRC)	17	14	12					
	•	-	-					
	•	-	-					
	-	•	-					
	•	•	•					
sor	•	•	•					
Mix	•	-	-					
ching	•	•	-					
	-	-	•					
rectionality	•	-	-					
rectionality	-	•	-					
	-	-	•					
l Optimizer II	•	-	-					
er	-	•	-					
	•	۲	0					
	•	۲	0					
on	•	•	-					
	•	۲	0					
	•	•	•					
	•	•	•					
	•	•	•					
ice Manager	•	•	•					
(88 only)	•	۲	0					
near - 88 only)	•	•	۲					
tor	•	•	•					

	RE967-DWT RE977-DWT RE988-DWT	RE767-DWT RE777-DWT RE788-DWT	RE567-DWT RE577-DWT RE588-DWT
FUNCTIONAL FEATURES			
Synchronized Push Button*	•	•	•
Synchronized Volume Control**	•	•	•
Smart Start	•	•	•
Phone Now	•	•	•
Comfort Phone	•	•	•
Ear-to-ear Communication	•	•	•
Direct Audio Streaming (iOS and Android***)	•	•	•
ReSound Wireless Accessory compatibility	•	•	•
ReSound Control™ app (Phone Clip+ is required)	•	•	•
ReSound Smart 3D™ app	•	•	•
RESOUND ASSIST			
Live Assistance	•	•	•
Remote Fine-tuning	•	•	•
Remote Firmware Updates	•	•	•
FITTING FEATURES			
Fitting Software ReSound Smart Fit™ 1.6 or higher	•	•	•
Available Gain Handles	10	8	6
Fully Flexible Programs	4	4	4
Auto DFS	•	•	•
Onboard Analyzer II	•	•	•
Noahlink Wireless	•	•	•

* Also including functionality for synchronized Push Button Volume Control - for 67 models only ** For 77 and 88 models only


***Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer and service carrier. ReSound cannot guarantee compatibility with all Android devices.

ReSound LiNX Quattro Custom Models




● Ultimate ● Advanced O Basic


MODEL	RE9CIC-W	RE7CIC-W	RE5CIC-W	RE9MIH-W; RE9MIH-WT	RE7MIH-W; RE7MIH-WT	RE5MIH-W; RE5MIH-W1
DEVICE CONFIGURATIONS	I	1	1		1	,
Battery size		10A			312/13	
Receiver Power levels		LP, MP, HP & UP	>		MP, HP & UP	
AUDIOLOGICAL FEATURES						
WARP compression (WDRC) - number of channels	17	14	12	17	14	12
Binaural Environmental Optimizer II	•	-	-	•	-	-
Environmental Optimizer	-	•	-	-	•	-
Noise Tracker II	•	۲	0	•	۲	0
Expansion	•	۲	0	•	۲	0
Impulse Noise Reduction	•	•	-	•	•	-
Sound Shaper	•	•	•	•	•	•
DFS Ultra II	•	•	•	•	•	•
Music Mode	•	•	•	•	•	•
Synchronized Acceptance Manager	•	•	•	•	•	•
Low Frequency Boost (Only UP)	•	•	0	•	•	0
Amplification Strategy (WDRC/Semi-Linear/Linear - Only UP)	•	•	۲	•	•	۲
Tinnitus Sound Generator	•	•	•	•	•	•
FUNCTIONAL FEATURES						
Synchronized Push Button *	•	•	•	•	•	•
Synchronized Volume Control	-	-	-	•	•	•
Smart Start	•	•	•	•	•	•
Phone Now	•	•	•	•	•	•
Comfort Phone	•	•	•	•	•	•
Ear-to-ear Communication	•	•	•	•	•	•
Direct audio streaming (iOS and Android**)	•	•	•	•	•	•
ReSound Wireless Accessory compatibility	•	•	•	•	•	•
ReSound Control™ app (Phone Clip+ is required)	•	•	•	•	•	•
ReSound Smart 3D™ app	•	•	•	•	•	•
RESOUND ASSIST		_				
Live Assistance	•	•	•	•	•	•
Remote Fine-tuning	•	•	•	•	•	•
Remote Firmware Updates	•	•	•	•	•	•
FITTING FEATURES						
Fitting Software ReSound Smart Fit™1.6 or higher	•	•	•	•	•	•
Available Gain Handles	10	8	6	10	8	6
Fully Flexible Programs	4	4	4	4	4	4
Auto DFS	•	•	•	•	•	•
Onboard Analyzer II	•	•	•	•	•	•
Noahlink Wireless	•	•	•	•	•	•














* Also including functionalit	y for synchronized Push Button Volume Control


**Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer and service carrier. ReSound cannot guarantee compatibility with all Android devices.


ReSound LiNX Ouattro Custom Models

ReSound LiNX Quattro Custom Models							
MODEL	RE9ITC-DW; RE9ITC-DWT	RE7ITC-DW; RE7ITC-DWT	RE5ITC-DW; RE5ITC-DWT	RE9ITE-DW; RE9ITE-DWT	RE7ITE-DW; RE7ITE-DWT	RE5ITE-DW; RE5ITE-DW1	
DEVICE CONFIGURATIONS			RESITC-DWT				
Battery size		312			312/13*		
Receiver Power levels		LP [†] , MP, HP & U	D		MP, HP & UP		
AUDIOLOGICAL FEATURES		<u>LP', MP, HP & U</u>	2				
WARP Compression (WDRC) - number of channels	17	14	12	17	14	12	
Binaural Directionality III	-	-	-	•	-	-	
Natural Directionality II	•	•	•	•	•	•	
Spatial Sense	-	_	_	•	-	_	
Binaural Directionality	-	_	_	_	•	-	
Directional Mix Processor	•	•	•	•	•	•	
Adjustable Directional Mix	•	_	_	•	_	_	
Synchronized soft switching	_	_	_	•	•	-	
Soft Switching	•	•	•	_	-	•	
Autoscope Adaptive Directionality	•	_	_	•	-	_	
Multiscope Adaptive Directionality	-	•	_	-	•	-	
Adaptive Directionality	-	_	•	_	_	•	
Binaural Environmental Optimizer II		_	_	•	-	_	
Environmental Optimizer II	•	-	-	-	-	-	
Environmental Optimizer	_	•	-	-	•	-	
Noise Tracker II	•	۲	0	•	۲	0	
Expansion	•	۲	0	•	۲	0	
Impulse Noise Reduction	•	•	-	•	•	-	
Wind Guard	•	۲	0	•	۲	0	
Sound Shaper	•	•	•	•	•	•	
DFS Ultra II	•	•	•	•	•	•	
Music Mode	•	•	•	•	•	•	
Synchronized Acceptance Manager	-	-	-	•	•	•	
Acceptance Manager	•	•	•	-	-	-	
Low Frequency Boost (Only UP)	•	•	•	•	•	0	
Amplification Strategy (WDRC/Semi-Linear/Linear - Only UP)	•	•	۲	•	•	۲	
Tinnitus Sound Generator	•	•	•	•	•	•	
FUNCTIONAL FEATURES							
Synchronized Push Button**	-	-	-	•	•	•	
Synchronized Volume Control	-	-	-	•	•	•	
Smart Start	•	•	•	•	•	•	
Phone Now	•	•	•	•	•	•	
Comfort Phone	-	-	-	•	•	•	
Ear-to-ear Communication	-	-	-	•	•	•	
Direct audio streaming (iOS and Android***)	•	•	•	•	•	•	
ReSound Wireless Accessory compatibility	•	•	•	•	•	•	
ReSound Control™ app (Phone Clip+ is required)	•	•	•	•	•	•	
ReSound Smart 3D™ app	•	•	•	•	•	•	
RESOUND ASSIST	_	_	_	-		_	
Live Assistance	•	•	•	•	•	•	
Remote Fine-tuning	•	•	•	•	•	•	
Remote Firmware Updates	•	•	•	•	•	•	
FITTING FEATURES		-		-		Ť	
Fitting Software ReSound Smart Fit™ 1.6 or higher	•	•	•	•	•	•	
Available Gain Handles	10	8	6	10	8	6	
Fully Flexible Programs	4	4	4	4	4	4	
Auto DFS	4	4	4	4	4	4	
	•	•	•	•	•	•	
Onboard Analyzer II Noahlink Wireless	•	•	•	•	•	•	
INOUTION VIICICSS	•	-		-	-	-	

ITC Fitting range

Fitting Range - Closed







Fitting Range - Closed

ITE Fitting range

Frequency (Hz) 500 1000 2000 4000 8000



Fitting Range - Closed



†LP - Not available for ITC-DWT

*HS size 13 not available in Canada.

** Also including functionality for synchronized Push Button Volume Control

***Full streaming compatibility with Android devices requires minimum Android v10 and Bluetooth 5.0 and that functionality has been enabled by the phone manufacturer • • • • • and service carrier. ReSound cannot guarantee compatibility with all Android devices.

NOTES:	Call Absolute Hearing Solutions 614-452-4180 NOTES:		
NOTES			NOTES

At ReSound, we understand how important it is for you to have a partner you can trust - one that not only has the latest technology, but also a shared commitment to go that extra mile to help people with hearing loss successfully adapt to life with hearing aids. So it's good to know we've been keeping our promise to help make life sound better for over 150 years, enabling you to help your patients hear more, do more and be more than they ever thought possible.

ReSound is part of the GN Group – pioneering great sound from world-leading ReSound hearing aids to Jabra office headsets and sports headphones. Founded in 1869, employing over 5,000 people, and listed on NASDAQ OMX Copenhagen. GN makes life sound better.

Find out how you can help your patients experience confidence in the finer details with ReSound LiNX Quattro at pro.resound.com

facebook.com/resoundhearing twitter.com/resoundus youtube.com/resoundus

© 2020 GN Hearing A/S. All rights reserved. ReSound is a trademark of GN Hearing A/S. Apple, the Apple logo, iPhone, iPad, iPod touch, Apple Watch and FaceTime are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc., registered in the U.S. and other countries. Android, Google Play and the Google Play logo are trademarks of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License. Dolby and the double-D symbol are registered trademarks of Dolby Laboratories. The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc.



ReSound GN

Manufacturer according to FDA:

GN ReSound North America

8001 E Bloomington Freeway Bloomington, MN 55420 USA 1-800-248-4327 pro.resound.com

ReSound Government Services

8001 E Bloomington Freeway Bloomington, MN 55420 USA 1-800-392-9932 gs.resound.com

Manufacturer according to Health Canada:

ReSound Canada

2 East Beaver Creek Road, Building 3 Richmond Hill, ON L4B 2N3 Canada 1-888-737-6863 resoundpro.com



Absolute Hearing Solutions LLC absolutehearin9@att.net

750 Cross Pointe Road Suite F Gahanna, Ohio 43230

Phone: 614-452-4260 Toll Free: 888-803-2159 Fax: 614-577-0481 www.ah soluteh earings olutions.com